

**Safety Data Sheet****MAPEFLOOR I 302 SL NA PART A BASE T**

Safety Data Sheet dated: 06/10/2021 - version 3

Date of first edition: 07/02/2018

**1. Identification****Product identifier**

Mixture identification:

Trade name: MAPEFLOOR I 302 SL NA PART A BASE T

Other means of identification

Trade code: 905HX0920

**Recommended use and restrictions on use**

Recommended use: Epoxy resins

Restrictions on use: N.A.

**Supplier's details**

Company: MAPEI INC. (Canada)

2900 Francis-Hughes Avenue

H7L 3J5 - Laval - QC - CAN

**Emergency phone number**

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

**2. Hazard identification****Classification of the product**

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

**Label elements****Pictograms and Signal Words**

Warning

**Hazard statements:**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust or mist.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P321	Specific treatment (see supplementary instructions on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

#### Other hazards

None

#### Ingredient(s) with unknown acute toxicity

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

### 3. Composition/information on ingredients

#### Substances

N.A.

#### Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

#### List of components

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
50-75 %	Silica Sand	CAS:14808-60-7	STOT RE 1, H372; Carc. 1A, H350	
25-50 %	Bisphenol A epoxy resin	CAS:25085-99-8	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Aquatic Chronic 2, H411; Skin Sens. 1B, H317	
5-10 %	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	CAS:28064-14-4	Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 2, H411	N.A.
2.5-5 %	Alkyl epoxy resin	CAS:68609-97-2	Skin Irrit. 2, H315; Skin Sens. 1, H317	
1-2.5 %	Benzyl alcohol	CAS:100-51-6	Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2A, H319	

The actual concentration of the components listed above is withheld as a trade secret.

### 4. First-aid measures

#### Description of necessary first-aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

#### Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

#### Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

## 5. Fire-fighting measures

### Suitable and unsuitable extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO<sub>2</sub>).

Unsuitable extinguishing media:

- None in particular.

### Specific hazards arising from the hazardous product

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: N.A.
- Explosive properties: N.A.
- Oxidizing properties: N.A.

### Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus.
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove persons to safety.
- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Limit leakages with earth or sand.

### Methods and material for containment and cleaning up

- Suitable material for taking up: absorbing material, organic, sand
- Retain contaminated washing water and dispose it.

## 7. Handling and storage

### Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Exercise the greatest care when handling or opening the container.
- Don't use empty container before they have been cleaned.
- Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
- Contaminated clothing should be changed before entering eating areas.
- Do not eat or drink while working.
- See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

- Keep away from food, drink and feed.

Incompatible materials:

- None in particular.

Instructions as regards storage premises:

- Adequately ventilated premises.

## 8. Exposure controls/personal protection

### Control parameters

#### List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m <sup>3</sup>	Long Term ppm	Short Term mg/m <sup>3</sup>	Short Term ppm	Behaviour	Note
Silica Sand	ACGIH			0,025					A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;
Benzyl alcohol	MAK	GERMANY	22	5					
	MAK	SWITZERLAND	22	5					

### Appropriate engineering controls

N.A.

### Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

---

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: Beige

Odour: Characteristic

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point: 94 °C (201 °F)

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available

Vapour pressure: No data available

Relative density: No data available

Solubility in water: Insoluble

Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available

Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available

Oxidizing properties: No data available

Solid/gas flammability: No data available

### Other information

Substance Groups relevant properties No data available

Miscibility: No data available

Fat Solubility: No data available

Conductivity: No data available

---

## 10. Stability and reactivity

### Reactivity

Stable under normal conditions

### Chemical stability

Data not available.

### Possibility of hazardous reactions

None.

### Conditions to avoid

Stable under normal conditions.

### Incompatible materials

None in particular.

### Hazardous decomposition products

None.

---

## 11. Toxicological information

## Information on toxicological effects

### Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

### Toxicological information on main components of the mixture:

Silica Sand a) acute toxicity LD50 Oral Rat = 500 mg/kg

PHENOL, POLYMER WITH a) acute toxicity LD50 Skin Rabbit > 5000,00000 mg/kg  
FORMALDEHYDE,  
GLYCIDYL ETHER

LD50 Oral Rat > 11400,00000 mg/kg

Alkyl epoxy resin a) acute toxicity LD50 Skin Rabbit > 3987 mg/kg  
LD50 Oral Rat = 17100 mg/kg

Benzyl alcohol a) acute toxicity LD50 Skin Rabbit = 2000,00000 mg/kg  
LC50 Inhalation Rat = 8,80000 mg/l 4h  
LD50 Oral Rat = 1230 mg/kg  
LD50 Skin Rabbit = 2 g/kg  
LD50 Oral Rat = 1230 mg/kg

**If not differently specified, the information required in the regulation and listed below must be considered as N.A.**

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

Toxicological kinetics, metabolism and distribution information

- i) STOT-repeated exposure
- j) aspiration hazard

### Substance(s) listed on the IARC Monographs:

Silica Sand Group 1

### Substance(s) listed as OSHA Carcinogen(s):

Silica Sand

### Substance(s) listed as NIOSH Carcinogen(s):

Silica Sand

### Substance(s) listed on the NTP report on Carcinogens:

Silica Sand

---

## 12. Ecological information

### Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

### List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
Silica Sand	CAS: 14808-60-7	a) Aquatic acute toxicity : LC50 carp > 10000,00000 mg/L 72h
Benzyl alcohol	CAS: 100-51-6	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 460 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 10 mg/L 96h EPA

## Persistence and degradability

N.A.

## Bioaccumulative potential

N.A.

## Mobility in soil

N.A.

## Other adverse effects

N.A.

---

## 13. Disposal considerations

### Safe handling and methods for disposal

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

#### Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

#### Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

#### Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

---

## 14. Transport information

### UN number

TDG-UN number: UN3082

ADR-UN number: 3082

DOT-UN Number: UN3082

IATA-Un number: 3082

IMDG-Un number: 3082

### UN proper shipping name

TDG-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin - PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER)

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin - PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER)

DOT-Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A epoxy resin - PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER)

IATA-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin - PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER)

IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin - PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER)

### Transport hazard class(es)

TDG-Class: 9

ADR-Class: 9

DOT-Hazard Class: 9

IATA-Class: 9

IMDG-Class: 9

### Packing group

TDG-Packing Group: III

ADR-Packing Group: III

DOT Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

#### **Environmental hazards**

Marine pollutant: Yes

Environmental Pollutant: N.A.

#### **Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)**

N.A.

#### **Special precautions in connection with transport or conveyance**

TDG:

TDG Special provisions: 16, 99

Department of Transportation (DOT):

DOT-Special Provision(s): 8, 146, 173, 335, IB3, T4, TP1, TP29

DOT-Label(s): 9

DOT-Symbol: N/A

DOT-Cargo Aircraft: N/A

DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A

DOT-Non-Bulk: N/A

Road and Rail ( ADR-RID ) :

ADR exempt: No

ADR-Label: 9

ADR-Hazard identification number: 90

ADR-Transport category (Tunnel restriction code): 3 (E)

Air ( IATA ) :

IATA-Passenger Aircraft: 964

IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisioning: A97 A158 A197

Sea ( IMDG ) :

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 274 335

IMDG-Page: N/A

IMDG-Label: N/A

IMDG-EMS: F-A, S-F

IMDG-MFAG: N/A

---

## **15. Regulatory information**

### **Canada - Federal regulations**

#### **DSL - Domestic Substances List**

##### **DSL Inventory:**

All the substances are listed in the DSL.

#### **NDSL - Non Domestic Substances List**

##### **NDSL Inventory:**

No substances listed

#### **NPRI - National Pollutant Release Inventory**

##### **Substances listed in NPRI:**

No substances listed

### **USA - Federal regulations**

#### **TSCA - Toxic Substances Control Act**

##### **TSCA inventory:**

All the components are listed on the TSCA inventory

##### **TSCA listed substances:**

Silica Sand is listed in TSCA Section 8b

Bisphenol A epoxy resin is listed in TSCA Section 8b

PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER is listed in TSCA Section 8b

Alkyl epoxy resin is listed in TSCA Section 8b

Benzyl alcohol is listed in TSCA Section 8b

#### **SARA - Superfund Amendments and Reauthorization Act**

##### **Section 302 - Extremely Hazardous Substances:**

No substances listed

##### **Section 304 - Hazardous substances:**

No substances listed

##### **Section 313 - Toxic chemical list:**

No substances listed

#### **CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act**

##### **Substance(s) listed under CERCLA:**

No substances listed

#### **CAA - Clean Air Act**

##### **CAA listed substances:**

Benzyl alcohol is listed in CAA Section 112(b) - HON

#### **CWA - Clean Water Act**

##### **CWA listed substances:**

No substances listed

#### **USA - State specific regulations**

##### **California Proposition 65**

##### **Substance(s) listed under California Proposition 65:**

Silica Sand Listed as carcinogen

##### **Massachusetts Right to know**

##### **Substance(s) listed under Massachusetts Right to know:**

Silica Sand

Benzyl alcohol

##### **Pennsylvania Right to know**

##### **Substance(s) listed under Pennsylvania Right to know:**

Silica Sand

Benzyl alcohol

##### **New Jersey Right to know**

##### **Substance(s) listed under New Jersey Right to know:**

Silica Sand

---

## **16. Other information**

Safety Data Sheet dated: 6/10/2021 - version 3

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

#### **Code**

#### **Description**

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

#### **Legend to abbreviations and acronyms used in the safety data sheet:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.  
IMDG: International Maritime Code for Dangerous Goods.  
IATA: International Air Transport Association.  
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
ICAO: International Civil Aviation Organization.  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).  
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
CLP: Classification, Labeling, Packaging.  
EINECS: European Inventory of Existing Commercial Chemical Substances.  
INCI: International Nomenclature of Cosmetic Ingredients.  
CAS: Chemical Abstracts Service (division of the American Chemical Society).  
GefStoffVO: Ordinance on Hazardous Substances, Germany.  
LC50: Lethal concentration, for 50 percent of test population.  
LD50: Lethal dose, for 50 percent of test population.  
DNEL: Derived No Effect Level.  
PNEC: Predicted No Effect Concentration.  
TLV: Threshold Limiting Value.  
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).  
STEL: Short Term Exposure limit.  
STOT: Specific Target Organ Toxicity.  
WGK: German Water Hazard Class.  
KSt: Explosion coefficient.

**Paragraphs modified from the previous revision:**

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 6. ACCIDENTAL RELEASE MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 15. REGULATORY INFORMATION